

HVAC CONTROL PRODUCTS – NORTH AMERICA

# VG1000 Series Ball Valve Selection Guide





Creating a more comfortable, safe and sustainable world.

How to build factory assembly codes using this guide

					Actuator Type											
					Non-Spring Return				Spring Return Port A Open <sup>2</sup>				Spring Return			
					M9124				M9220							
					On / Off and Floating Point 0 (2) to 10 VDC 0 (4) to 20 mA (w/500 ohm resistor)				On / Off and Floating Point 120V On / Off 24V On / Off 0 (2) to 10 VDC 0 (4) to 20 mA (w/500 ohm resistor)				On / Off and Floating Point			

- Standard Fluid Temperature Range
- NPT Threaded

Spring Return Port A Open      Spring Return Port A Closed

Factory Assembled Valve + Actuator Combinations Matrix

VG1000 SELECTION GUIDE 4



- High Fluid Temperature Range
- NPT Threaded

		Ball Valves with VA9104 Series Actuators
		Ball Valves with M9106(9) Series Actuators
		Ball Valves with VA9203 Series Actuators
		Ball Valves with VA9208 Series Actuators
		Motorized Ball Valve Assembly with Weather Shield (field assembly)

[illegible]

1 VA9xxx Series Actuators are direct mount actuators, M9106 and M9109 valve/actuator assemblies include the M9000-520 linkage  
2  
3 For 3-Way valves, the first Cv listed is for Port A (Coil). The second Cv listed in parenthesis is for Port B (Bypass)  
4  
5 For Ball valve and actuator factory assemblies combine valve code number and actuator valve assembly code.  
6  
7 Example: VG1245ADH9744GA is 1/2 inch two-way ball valve, 12 Cv, NPT end connections, Stainless Steel trim with VA9104 Series non-spring  
8 return electrical actuator with 24 VAC floating point control without time out with screw terminal electrical connections.

- Standard Fluid Temperature Range
- Sweat and Press Connected

System. Association of Variables. A Systemic Comparison Method.

Example: VG1895AD+9T4AGA is 1/2 inch three-way ball valve, 1.2 Cv, Press end connections, stainless steel trim with non-spring return electric actuator with 24 VAC floating point control without time out with screw terminal electrical connections.

Factory Assembled  
Motorized Valve Assemblies

- High Fluid Temperature Range
- ASME Class 150 Flange Connected

		M9124 Actuator Installed on 2 1/2 thru 4 inch. ASME Flanged Ball Valves using M9000-518 Linkage
		M9220 Actuator Installed on 2 1/2 thru 4 inch. ASME Flanged Ball Valves using M9000-519 Linkage
		Field Assembled M9124 Actuator, M9000-518 Linkage and M9000-330 Weather Shield on ASME Flanged Ball Valve
		Field Assembled M9220 Actuator, M9000-519 Linkage and M9000-340 Weather Shield on Flanged Ball Valve (field assembly)

<div><div><div>• ASME Class 150 Flange Connected</div><div>• High Fluid Temperature Range</div><div>• Stainless Steel Trim</div><div>• Close Off Pressure</div><div>2-Way = 100 PSID</div><div>3-Way = 50 PSID</div><div>• Fluid Temperature Limits:</div><div>-22 to 284°F (-30 to 140°C)</div></div></div>					Actuator Type																			
					Non-Spring Return				Spring Return Port A Open				Spring Return Port A Closed											
					M9124 <sup>1</sup>				M9220 <sup>2</sup>				M9220 <sup>2</sup>											
					Control Input				On / Off and Floating Point	0 (2) to 10 VDC	0 (4) to 20 mA (w/500 ohm resistor)	On / Off and Floating Point	120V On / Off	24V On / Off	0 (2) to 10 VDC	0 (4) to 20 mA (w/500 ohm resistor)	On / Off and Floating Point	120V On / Off	24V On / Off	0 (2) to 10 VDC	0 (4) to 20 mA (w/500 ohm resistor)			
1 SPDT, 5.0(2.9) A @ 240 V																								
Auxiliary Switches: 2 SPDT, 5.0(2.9) A @ 240 V									■		■		■		■		■							
2 SPDT, 3.0(1.5) A @ 24 VAC						■		■								■								
Inch	DN (mm)	Cv <sup>3</sup>	2-Way ANSI Flange	3-Way ANSI Flange																				
2 1/2	65	47 (29)	VG12A5GS	VG18A5GS	■	■	■	■	■	■	■	■	■	■	■	■	■							
		74 (47)	VG12A5GT	VG18A5GT	■	■	■	■	■	■	■	■	■	■	■	■	■							
		117 (74)	VG12A5GU	VG18A5GU	■	■	■	■	■	■	■	■	■	■	■	■	■							
3	80	74 (47)	VG12A5HT	VG18A5HT	■	■	■	■	■	■	■	■	■	■	■	■	■							
		117 (74)	VG12A5HU	VG18A5HU	■	■	■	■	■	■	■	■	■	■	■	■	■							
		176 (88)	VG12A5HV	VG18A5HV	■	■	■	■	■	■	■	■	■	■	■	■	■							
		211 (105)	VG12A5HW	VG18A5HW	■	■	■	■	■	■	■	■	■	■	■	■	■							
4	100	117 (74)	VG12A5JU	VG18A5JU	■	■	■	■	■	■	■	■	■	■	■	■								
		176 (88)	VG12A5JV	VG18A5JV	■	■	■	■	■	■	■	■	■	■	■	■	■							
MOTORIZED VALVE ASSEMBLY CODE <sup>4</sup> = VALVE CODE + FACTORY ASSEMBLY CODE					+924AGA	+924AGC	+924GGA	+924GGC	+92NAGA	+92NAGC	+92NBAA	+92NBAC	+92NBGA	+92NBGC	+92NGGA	+92NGGC	+94NAGA	+94NAGC	+94NBAA	+94NBAC	+94NBGA	+94NBGC	+94NGGA	+94NGGC
Example: VG18A5HU+92NGGA																								
Position Feedback:																								
0(2) to 10 VDC Position Feedback							■	■							■	■							■	■
Power Requirements:																								
24 VAC +25%/-20%, Class 2, SELV																								
24 VAC +25%/-15%, VDC +/- 10%					■	■	■	■																
24 VAC +/- 20%, VDC +/- 10%									■	■			■	■	■	■	■	■			■	■	■	■
24 VAC +/- 25%, VDC +/- 10%																								
120 VAC +10%/-15% at 60 Hz											■	■							■	■				
85 to 264 VAC at 50/60 Hz																								
Electrical Connections:																								
Screw Terminals							■	■																
48 in. (1.2 m) 19 AWG Plenum Cable																								
120 in. (3.05 m) 19 AWG Plenum Cable																								
1/4 in. Spade Terminals					■	■																		
48 in. (1.2 m) 18 AWG Appliance Cable									■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Weather Shield Options (For Field Assembly Only)																								
M9000-330 Weather Shield					■	■	■	■																
M9000-340 Weather Shield									■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

1 The M9124 assemblies include the M9000-518 Linkage  
2 The M9220 assemblies include the M9000-519 Linkage  
3 For 3-Way valves, the first Cv listed is for Port A (Coil). The second Cv listed in parenthesis is for Port B (Bypass)  
4 For Ball Valve and actuator factory assemblies combine valve code number and actuator valve assembly code.  
Example: VG18A5HU+92NGGA is a 3 inch, 3-Way ball valve, 117 Cv thru Port A and 74 Cv thru Port B, ASME Class 150 flanged end connections, stainless steel trim with M9220 spring return actuator, with 0(2) to 10 VDC or 0(4) to 20ma proportional control with 48 in. (1.2m) 18 AWG Appliance Cable, assembled for spring return port "A" open.



Special Configurations:  
Field Assembled  
Weather Applications

Actuator Options	1 SPDT, 5.0(2.9) A @ 240 V											
	Auxiliary Switches: 2 SPDT, 5.0(2.9) A @ 240 V											
	2 SPDT, 3.0(1.5) A @ 24 VAC							■		■		
Valve Type	Inch	DN (mm)	Cv <sup>1</sup>	2-Way Brass Trim	3-Way Brass Trim	2-Way Stainless Steel Trim	3-Way Stainless Steel Trim					
	1/2	15	1.2 (0.7)	VG1241AD	VG1841AD	VG1245AD	VG1845AD	■	■	■	■	
			1.9 (1.2)	VG1241AE	VG1841AE	VG1245AE	VG1845AE	■	■	■	■	
			2.9 (1.9)	VG1241AF	VG1841AF	VG1245AF	VG1845AF	■	■	■	■	
			4.7 (2.9)	VG1241AG	VG1841AG	VG1245AG	VG1845AG	■	■	■	■	
			7.4 (4.7)	VG1241AL	VG1841AL	VG1245AL	VG1845AL	■	■	■	■	
	3/4	20	11.7 (5.8)	VG1241AN	VG1841AN	VG1245AN	VG1845AN	■	■	■	■	
			4.7 (2.9)	VG1241BG	VG1841BG	VG1245BG	VG1845BG	■	■	■	■	
			7.4 (4.7)	VG1241BL	VG1841BL	VG1245BL	VG1845BL	■	■	■	■	
	1	25	11.7 (5.8)	VG1241BN	VG1841BN	VG1245BN	VG1845BN	■	■	■	■	
			7.4 (4.7)	VG1241CL	VG1841CL	VG1245CL	VG1845CL	■	■	■	■	
			11.7 (7.4)	VG1241CN	VG1841CN	VG1245CN	VG1845CN	■	■	■	■	
	1 1/4	32	18.7 (9.4)	VG1241CP	VG1841CP	VG1245CP	VG1845CP	■	■	■	■	
			11.7 (7.4)	VG1241DN	VG1841DN	VG1245DN	VG1845DN	■	■	■	■	
			18.7 (11.7)	VG1241DP	VG1841DP	VG1245DP	VG1845DP	■	■	■	■	
	1 1/2	40	29.2 (14.6)	VG1241DR	VG1841DR	VG1245DR	VG1845DR	■	■	■	■	
			18.7 (11.7)	VG1241EP	VG1841EP	VG1245EP	VG1845EP	■	■	■	■	
			29.2 (18.7)	VG1241ER	VG1841ER	VG1245ER	VG1845ER	■	■	■	■	
	2	50	46.8 (23.4)	VG1241ES	VG1841ES	VG1245ES	VG1845ES	■	■	■	■	
			29.2 (18.7)	VG1241FR	VG1841FR	VG1245FR	VG1845FR	■	■	■	■	
			46.8 (29.2)	VG1241FS	VG1841FS	VG1245FS	VG1845FS	■	■	■	■	
	Additional Actuator and Accessory Reference Information			73.7 (36.8)	VG1241FT	VG1841FT	VG1245FT	VG1845FT	■	■	■	■
		VALVE CODE							ACTUATOR CODE (For Field Assembly)			
									M9108-AGA-2			
									M9108-AGC-2			
									M9108-GGA-2			
									M9108-GGC-2			
Position Feedback:												
0(2) to 10 VDC Position Feedback									■	■		
Power Requirements:												
24 VAC +25%/-20%, Class 2, SELV												
24 VAC +25%/-15%, VDC +/- 10%							■	■	■	■		
24 VAC +/- 20%, VDC +/- 10%												
24 VAC +/- 25%, VDC +/- 10%												
120 VAC +10%/-15% at 60 Hz												
85 to 264 VAC at 50/60 Hz												
Electrical Connections:												
Screw Terminals							■	■	■	■		
48 in. (1.2 m) 19 AWG Plenum Cable												
120 in. (3.05 m) 19 AWG Plenum Cable												
1/4 in. Spade Terminals												
48 in. (1.2 m) 18 AWG Appliance Cable												
Weather Shield Options (For Field Assembly Only)												
M9000-330 Weather Shield + M9000-516 Linkage							■	■	■	■		

Valid Field Assembly Combinations  
VG1000 Series Ball Valves, M(VA)9000 Series Actuators, Linkage Kits, Weather Shields

Valve Size in. (mm)	NPT End Connection	Sweat End Connection	Press End Connection	Actuator Base Code Number <sup>1</sup>	Linkage Kit Code Number	Weather Shield Code Number
1/2 (DN15)	VG1241Ax VG1245Ax VG1841Ax VG1845Ax	VG1275Ax VG1875Ax	VG1295Ax VG1895Ax	VA9104 <sup>2</sup>	Non-required (Fluid Temperatures ≤212°F)	M9000-341 (When using Weather Shield M9000-561 Thermal Barrier is not needed)
					M9000-561 (Fluid Temperatures >212°F)	
				M9104 <sup>2</sup>	M9000-551 (Fluid Temperatures ≤212°F)	
					M9000-551 and M9000-561 (Fluid Temperatures >212°F)	
				M9106 <sup>2</sup>	M9000-520	
				M9108	M9000-516	M9000-330
				VA9203	Non-required (Fluid Temperatures ≤212°F)	M9000-341 (When using Weather Shield M9000-561 Thermal Barrier is not needed)
					M9000-561 (Fluid Temperatures >212°F)	
				M9203	M9000-560 (Fluid Temperatures ≤212°F)	
	M9000-560 and M9000-561 (Fluid Temperatures >212°F)					
3/4 (DN20)	VG1241Bx VG1245Bx VG1841Bx VG1845Bx	VG1275Bx VG1875Bx	VG1295Bx VG1895Bx	VA9104 <sup>2</sup>	Non-required (Fluid Temperatures ≤212°F)	M9000-341 (When using Weather Shield M9000-561 Thermal Barrier is not needed)
					M9000-561 (Fluid Temperatures >212°F)	
				M9104 <sup>2</sup>	M9000-551 (Fluid Temperatures ≤212°F)	
					M9000-551 and M9000-561 (Fluid Temperatures >212°F)	
				M9106 <sup>2</sup>	M9000-520	
				M9108	M9000-516	M9000-330
				VA9203	Non-required (Fluid Temperatures ≤212°F)	M9000-341 (When using Weather Shield M9000-561 Thermal Barrier is not needed)
					M9000-561 (Fluid Temperatures >212°F)	
				M9203	M9000-560 (Fluid Temperatures ≤212°F)	
	M9000-560 and M9000-561 (Fluid Temperatures >212°F)					
1 (DN25)	VG1241Cx VG1245Cx VG1841Cx VG1845Cx	VG1275Cx VG1875Cx	VG1295Cx VG1895Cx	VA9104 <sup>2</sup>	Non-required (Fluid Temperatures ≤212°F)	M9000-341 (When using Weather Shield M9000-561 Thermal Barrier is not needed)
					M9000-561 (Fluid Temperatures >212°F)	
				M9104 <sup>2</sup>	M9000-551 (Fluid Temperatures ≤212°F)	
					M9000-551 and M9000-561 (Fluid Temperatures >212°F)	
				M9106 <sup>2</sup>	M9000-520	
				M9108	M9000-516	M9000-330
				VA9203	Non-required (Fluid Temperatures ≤212°F)	M9000-341 (When using Weather Shield M9000-561 Thermal Barrier is not needed)
					M9000-561 (Fluid Temperatures >212°F)	
				M9203	M9000-560 (Fluid Temperatures ≤212°F)	
	M9000-560 and M9000-561 (Fluid Temperatures >212°F)					
1 1/4 (DN32)	VG1241Dx VG1245Dx VG1841Dx VG1845Dx			M9106 <sup>2</sup>	M9000-520	
				M9108	M9000-516	M9000-330
				VA9208	Non-required (Fluid Temperatures ≤212°F)	M9000-341 (When using Weather Shield M9000-561 Thermal Barrier is not needed)
					M9000-561 (Fluid Temperatures >212°F)	
				M9208	M9000-560 (Fluid Temperatures ≤212°F)	
	M9000-560 and M9000-561 (Fluid Temperatures >212°F)					
1 1/2 (DN40)	VG1241Ex VG1245Ex VG1841Ex VG1845Ex			M9106 <sup>2</sup>	M9000-520	
				M9108	M9000-516	M9000-330
				VA9208	Non-required (Fluid Temperatures ≤212°F)	M9000-341 (When using Weather Shield M9000-561 Thermal Barrier is not needed)
					M9000-561 (Fluid Temperatures >212°F)	
				M9208	M9000-560 (Fluid Temperatures ≤212°F)	
	M9000-560 and M9000-561 (Fluid Temperatures >212°F)					
2 (DN50)	VG1241Fx VG1245Fx VG1841Fx VG1845Fx			M9109 <sup>2</sup>	M9000-520	
				M9108	M9000-516	M9000-330
				VA9208	Non-required (Fluid Temperatures ≤212°F)	M9000-341 (When using Weather Shield M9000-561 Thermal Barrier is not needed)
					M9000-561 (Fluid Temperatures >212°F)	
				M9208	M9000-560 (Fluid Temperatures ≤212°F)	
	M9000-560 and M9000-561 (Fluid Temperatures >212°F)					
Flanged Ball Valves, ASME Class 150 Flange						
2 1/2 (DN65)	VG12A5Gx VG18A5Gx			M9124	M9000-518	M9000-330
				M9220	M9000-519	M9000-340
3 (DN80)	VG12A5Hx VG18A5Hx			M9124	M9000-518	M9000-330
				M9220	M9000-519	M9000-340
4 (DN100)	VG12A5Jx VG18A5Jx			M9124	M9000-518	M9000-330
				M9220	M9000-519	M9000-340

<sup>1</sup> The VA9104, M9104, M9106, M9108, M9109 and M9124 are non-spring return models. The VA9203, VA9208 and M9220 are spring return models.  
<sup>2</sup> To avoid excessive wear or drive time on the motor for VA9104, M9104, M9106 and M9109 AGx models, use a controller and/or software that provides a timeout function to remove the signal at the end of rotation (stall). The IGx and GGx models have an auto shutoff to avoid excessive wear or drive time on the motor

1 For 3-Way valves, the first Cv listed is for Port A (Coil). The second Cv listed in parenthesis is for Port B (Bypass).

VG1000 Series Ball Valve Accessories

	Code Number	Description	Qty
Ball Valve Linkages			
	M9000-551	VG1000 Ball Valve linkage (for use with M9104 Series actuators only)	1
	M9000-520	VG1000 Ball Valve linkage (for use with M9106, M9109 and M9206 Series actuators only)	1
	M9000-560	Ball Valve Linkage Kit for applying M9203, and M9208 Series Electric Actuators to VG1000 Series Valves	1
	M9000-561	Thermal Barrier Kit for M9000-560 Ball Valve Linkage. Extends M(VA)9104, M(VA)9203, and M(VA)9208 Series Electric Spring Return Actuators applications to include low pressure steam	1
	M9000-516	Ball Valve Linkage for Non-Spring Return, 1/2 to 2 in. VG1000 valves with 9 mm square stem	1
	M9000-518	Ball Valve Linkage for Non-Spring Return, 2 1/2 to 4 in. VG1000 flanged valves with 11 mm square stem	1
	M9000-519	Ball Valve Linkage for Spring Return, 2 1/2 to 4 in. VG1000 flanged Valves with 11 mm square stem	1

VG1000 Series Ball Valve Accessories

	Code Number	Description	Qty
Weather Shields for Ball Valves			
	M9000-341	Weather Shield Kit for VG1000 Series Ball Valve application of M(VA)9104, M(VA)9203, and M(VA)9208 Series Electric Spring Return Actuators	1
	M9000-330	NEMA 3R Weather Shield for VG1000 Series Non-Spring Return Ball Valves with M9000-516 or M9000-518 Linkage	1
	M9000-340	NEMA 3R Weather Shield for VG1000 Series Spring Ball Valves with M9000-517 or M9000-519 Linkage	1
Miscellaneous			
	M9000-155	Manual Handle for M9108[16][24][32] Series Actuators	1
	M9200-100	Threaded Conduit Adapters for 1/2 in. electrician's fittings (For use with M(VA)9208, M(VA)9210, and M(VA)9220 Series Actuators)	5
	M9000-607	Position Indicator for VG1000 Series Ball Valve Applications (For use with VA9203 and VA9208 Series Actuators)	5
	M9000-200	Commissioning Tool that provides a control signal to drive 24V On/Off, Floating, Proportional, and/or Resistive Electric Actuators	1



## Sizing Water Valves

**Two-Position Applications:** The valve is normally sized with the largest Cv available.

**Modulating Applications:** The valve should be sized to produce the required Cv with a pressure drop of one to two times the pressure drop across the coil at rated flow.

**Example:** Coil requires 14 gpm at 5 psi pressure drop. The valve should be selected to provide 14 gpm with a pressure drop across the valve between 5 and 10 psi (one to two times the pressure drop across the coil at the required flow).

**Solution:** From the table below a 1/2 in., 4.7 Cv valve will provide 14.1 gpm flow at a pressure drop across the valve of 9 psi. This valve should be selected as the valve will provide the needed flow with a pressure drop between one and two times the pressure drop across the coil at the required flow.

### VG1000 Ball Valves 1/2 through 2 inch

FLOW RATE IN GPM (GALLONS PER MINUTE)										
Cv	1.2	1.9	2.9	4.7	7.4	11.7	18.7	29.2	46.8	73.7
Pressure Drop (PSI)										
1	1.2	1.9	2.9	4.7	7.4	11.7	18.7	29.2	46.8	73.7
2	1.7	2.7	4.1	6.6	10.5	16.5	26.4	41.3	66.2	104.2
3	2.1	3.3	5.0	8.1	12.8	20.3	32.4	50.6	81.1	127.7
4	2.4	3.8	5.8	9.4	14.8	23.4	37.4	58.4	93.6	147.4
5	2.7	4.2	6.5	10.5	16.5	26.2	41.8	65.3	104.6	164.8
6	2.9	4.7	7.1	11.5	18.1	28.7	45.8	71.5	114.6	180.5
7	3.2	5.0	7.7	12.4	19.6	31.0	49.5	77.3	123.8	195.0
8	3.4	5.4	8.2	13.3	20.9	33.1	52.9	82.6	132.4	208.5
9	3.6	5.7	8.7	14.1	22.2	35.1	56.1	87.6	140.4	221.1
10	3.8	6.0	9.2	14.9	23.4	37.0	59.1	92.3	148.0	233.1
11	4.0	6.3	9.6	15.6	24.5	38.8	62.0	96.8	155.2	244.4
12	4.2	6.6	10.0	16.3	25.6	40.5	64.8	101.2	162.1	255.3
13	4.3	6.9	10.5	16.9	26.7	42.2	67.4	105.3	168.7	265.7
14	4.5	7.1	10.9	17.6	27.7	43.8	70.0	109.3	175.1	275.8
15	4.6	7.4	11.2	18.2	28.7	45.3	72.4	113.1	181.3	285.4
16	4.8	7.6	11.6	18.8	29.6	46.8	74.8	116.8	187.2	294.8
17	4.9	7.8	12.0	19.4	30.5	48.2	77.1	120.4	193.0	303.9
18	5.1	8.1	12.3	19.9	31.4	49.6	79.3	123.9	198.6	312.7
19	5.2	8.3	12.6	20.5	32.3	51.0	81.5	127.3	204.0	321.3
20	5.4	8.5	13.0	21.0	33.1	52.3	83.6	130.6	209.3	329.6
21	5.5	8.7	13.3	21.5	33.9	53.6	85.7	133.8	214.5	337.7
22	5.6	8.9	13.6	22.0	34.7	54.9	87.7	137.0	219.5	345.7
23	5.8	9.1	13.9	22.5	35.5	56.1	89.7	140.0	224.4	353.5
24	5.9	9.3	14.2	23.0	36.3	57.3	91.6	143.1	229.3	361.1
25	6.0	9.5	14.5	23.5	37.0	58.5	93.5	146.0	234.0	368.5
26	6.1	9.7	14.8	24.0	37.7	59.7	95.4	148.9	238.6	375.8
27	6.2	9.9	15.1	24.4	38.5	60.8	97.2	151.7	243.2	383.0
28	6.3	10.1	15.3	24.9	39.2	61.9	99.0	154.5	247.6	390.0
29	6.5	10.2	15.6	25.3	39.9	63.0	100.7	157.2	252.0	396.9
30	6.6	10.4	15.9	25.7	40.5	64.1	102.4	159.9	256.3	403.7

## Sizing Water Valves

**Two-Position Applications:** The valve is normally sized with the largest Cv available.

**Modulating Applications:** The valve should be sized to produce the required Cv with a pressure drop of one to two times the pressure drop across the coil at rated flow.

**Example:** Coil requires 180 gpm at 4 psi pressure drop. The valve should be selected to provide 180 gpm with a pressure drop across the valve between 4 and 8 psi (one to two times the pressure drop across the coil at the required flow).

**Solution:** From the table below a 74 Cv valve will provide 181 gpm flow at a pressure drop across the valve of 6 psi. This valve should be selected as the valve will provide the needed flow with a pressure drop between one and two times the pressure drop across the coil at the required flow.

### VG1000 Ball Valves 2-1/2 through 4 inch

FLOW RATE IN GPM (GALLONS PER MINUTE)					
Cv	47	74	117	176	211
Pressure Drop (PSI)					
1	47	74	117	176	211
2	66	105	165	249	298
3	81	128	203	305	365
4	94	148	234	352	422
5	105	165	262	394	472
6	115	181	287	431	517
7	124	196	310	466	558
8	133	209	331	498	597
9	141	222	351	528	633
10	149	234	370	557	667
11	156	245	388	584	700
12	163	256	405	610	731
13	169	267	422	635	761
14	176	277	438	659	789
15	182	287	453	682	817
16	188	296	468	704	844
17	194	305	482	726	870
18	199	314	496	747	895
19	205	323	510	767	920
20	210	331	523	787	944
21	215	339	536	807	967
22	220	347	549	826	990
23	225	355	561	844	1012
24	230	363	573	862	1034
25	235	370	585	880	1055
26	240	377	597	897	1076
27	244	385	608	915	1096
28	249	392	619	931	1117
29	253	399	630	948	1136
30	257	405	641	964	1156

## Sizing Steam Valves

**Two-Position Applications:** The valve is normally sized to be the same as the pipe using the largest Cv available for a given pipe size.

**Modulating Applications:** Select the valve to meet the BtuH requirements of the coil.

**Assumptions:**

- 1. The table assumes an atmospheric return.
- 2. Minimum coil BtuH calculated assuming a pressure drop across the valve of 50% of supply pressure.
- 3. Maximum coil BtuH calculated assuming a pressure drop across the valve of 80% of supply pressure.

### VG1000 Ball Valves 1/2 through 2 inch

Available Pipe Size NPT	1/2 in.		1/2 in.		1/2 in.		1/2 in. 3/4 in.		1/2 in. 3/4 in. 1 in.	
Cv	1.2		1.9		2.9		4.7		7.4	
Supply Pressure	MINIMUM COIL BTUH	MAXIMUM COIL BTUH	MINIMUM COIL BTUH	MAXIMUM COIL BTUH	MINIMUM COIL BTUH	MAXIMUM COIL BTUH	MINIMUM COIL BTUH	MAXIMUM COIL BTUH	MINIMUM COIL BTUH	MAXIMUM COIL BTUH
1	10,700	13,600	17,000	21,500	25,900	32,800	42,000	53,200	66,200	83,700
2	15,600	19,800	24,700	31,300	37,800	47,800	61,200	77,400	96,400	121,900
3	19,600	24,800	31,100	39,300	47,500	60,000	76,900	97,300	121,100	153,200
4	23,300	29,500	36,900	46,700	56,300	71,200	91,200	115,400	143,700	181,700
5	26,700	33,700	42,200	53,400	64,400	81,500	104,400	132,100	164,400	208,000
6	29,900	37,900	47,400	59,900	72,300	91,500	117,200	148,300	184,600	233,400
7	33,000	41,800	52,300	66,100	79,800	100,900	129,300	163,600	203,600	257,600
8	36,100	45,600	57,100	72,200	87,200	110,300	141,300	178,700	222,400	281,400
9	39,000	49,400	61,800	78,200	94,300	119,300	152,900	193,300	240,700	304,400
10	42,000	53,100	66,400	84,000	101,400	128,300	164,300	207,900	258,700	327,300
11	44,800	56,700	71,000	89,800	108,300	137,000	175,600	222,100	276,400	349,600
12	47,600	60,300	75,400	95,400	115,100	145,600	186,600	236,000	293,800	371,600
15	56,000	70,900	88,700	112,200	135,400	171,300	219,500	277,600	345,600	437,100

### VG1000 Ball Valves 1/2 through 2 inch

Available Pipe Size NPT	1/2 in. 3/4 in. 1 in.		1 in. 1 1/4 in. 1 1/2 in.		1 1/4 in. 1 1/2 in. 2 in.		1 1/2 in. 2 in.		2 in.	
Cv	11.7		18.7		29.2		46.8		73.7	
Supply Pressure	MINIMUM COIL BTUH	MAXIMUM COIL BTUH	MINIMUM COIL BTUH	MAXIMUM COIL BTUH	MINIMUM COIL BTUH	MAXIMUM COIL BTUH	MINIMUM COIL BTUH	MAXIMUM COIL BTUH	MINIMUM COIL BTUH	MAXIMUM COIL BTUH
1	104,700	132,400	167,300	211,600	261,200	330,400	416,800	527,200	659,200	833,800
2	152,400	192,700	243,500	308,000	380,300	481,000	606,900	767,600	959,800	1,214,100
3	191,500	242,300	306,100	387,200	478,000	604,600	762,800	964,900	1,206,400	1,526,000
4	227,100	287,300	363,000	459,200	566,800	717,000	904,600	1,144,300	1,430,700	1,809,700
5	260,000	328,900	415,600	525,700	648,900	820,800	1,035,600	1,309,900	1,637,800	2,071,700
6	291,800	369,100	466,400	589,900	728,200	921,200	1,162,200	1,470,100	1,838,100	2,325,000
7	322,000	407,300	514,600	650,900	803,500	1,016,400	1,282,400	1,622,100	2,028,100	2,565,400
8	351,700	444,900	562,100	711,000	877,700	1,110,200	1,400,800	1,771,800	2,215,400	2,802,200
9	380,500	481,300	608,200	769,300	949,600	1,201,200	1,515,500	1,917,000	2,396,800	3,031,800
10	409,100	517,500	653,800	827,000	1,021,000	1,291,400	1,629,300	2,061,000	2,576,900	3,259,500
11	437,000	552,800	698,500	883,500	1,090,700	1,379,600	1,740,600	2,201,700	2,752,800	3,482,100
12	464,500	587,500	742,400	939,000	1,159,200	1,466,300	1,850,000	2,340,100	2,925,900	3,700,900
15	546,400	691,100	873,200	1,104,600	1,363,600	1,724,800	2,176,100	2,752,600	3,441,600	4,353,300

## Sizing Steam Valves

**Two-Position Applications:** The valve is normally sized to be the same as the pipe using the largest Cv available for a given pipe size.

**Modulating Applications:** Select the valve to meet the BtuH requirements of the coil.

**Assumptions:**

- 1. The table assumes an atmospheric return.
- 2. Minimum coil BtuH calculated assuming a pressure drop across the valve of 50% of supply pressure.
- 3. Maximum coil BtuH calculated assuming a pressure drop across the valve of 80% of supply pressure.

### VG1000 Ball Valves 2 1/2 through 4 inch

Available Pipe Size NPT	2 1/2 in.		2 1/2 in. 3 in.		2 1/2 in. 3 in. 4 in.		3 in. 4 in.		3 in.	
Cv	47		74		117		176		211	
Supply Pressure	MINIMUM COIL BTUH	MAXIMUM COIL BTUH	MINIMUM COIL BTUH	MAXIMUM COIL BTUH	MINIMUM COIL BTUH	MAXIMUM COIL BTUH	MINIMUM COIL BTUH	MAXIMUM COIL BTUH	MINIMUM COIL BTUH	MAXIMUM COIL BTUH
1	420,400	531,800	661,900	837,200	1,046,500	1,323,700	1,574,200	1,991,300	1,887,300	2,387,200
2	612,100	774,200	963,700	1,219,000	1,523,700	1,927,300	2,292,000	2,899,200	2,747,800	3,475,800
3	769,400	973,200	1,211,300	1,532,200	1,915,200	2,422,600	2,881,000	3,644,200	3,454,000	4,368,900
4	912,400	1,154,100	1,436,500	1,817,100	2,271,300	2,873,000	3,416,600	4,321,700	4,096,100	5,181,100
5	1,044,500	1,321,200	1,644,500	2,080,100	2,600,100	3,288,800	3,911,200	4,947,300	4,689,000	5,931,200
6	1,172,200	1,482,700	1,845,600	2,334,500	2,918,000	3,691,000	4,389,400	5,552,200	5,262,300	6,656,400
7	1,293,400	1,636,000	2,036,400	2,575,800	3,219,700	4,072,600	4,843,300	6,126,300	5,806,400	7,344,600
8	1,412,800	1,787,000	2,224,400	2,813,600	3,516,900	4,448,600	5,290,400	6,691,900	6,342,500	8,022,700
9	1,528,500	1,933,400	2,406,600	3,044,100	3,805,000	4,813,000	5,723,800	7,240,100	6,862,000	8,679,900
10	1,643,300	2,078,700	2,587,400	3,272,800	4,090,800	5,174,500	6,153,700	7,783,900	7,377,500	9,331,900
11	1,755,500	2,220,600	2,764,000	3,496,200	4,370,100	5,527,800	6,573,900	8,315,400	7,881,200	9,969,000
12	1,865,900	2,360,200	2,937,800	3,716,000	4,644,800	5,875,300	6,987,100	8,838,100	8,376,600	10,595,600
15	2,194,800	2,776,200	3,455,600	4,371,100	5,463,600	6,911,000	8,218,800	10,396,000	9,853,200	12,463,400
20	2,724,500	3,446,300	4,289,700	5,426,100	6,782,400	8,579,100	10,202,500	12,905,300	12,231,500	15,471,700
25	3,245,700	4,105,500	5,110,300	6,464,000	8,079,700	10,220,200	12,154,100	15,373,900	14,571,200	18,431,200

# Key to the Factory Assembly Codes to Actuator and Accessory Mounting Kits

Factory Assembly Code	Actuator and Accessories being Mounted
+9T4AGA	VA9104-AGA-3S
+9A4AGA	VA9104-AGA-2S
+9T4IGA	VA9104-IGA-3S
+9A4IGA	VA9104-IGA-2S
+9T4GGA	VA9104-GGA-3S
+9A4GGA	VA9104-GGA-2S
+906AGA	M9106-AGA-2 with M9000-520 linkage
+906AGC	M9106-AGC-2 with M9000-520 linkage
+906IGA	M9106-IGA-2 with M9000-520 linkage
+906IGC	M9106-IGC-2 with M9000-520 linkage
+906GGA	M9106-GGA-2 with M9000-520 linkage
+906GGC	M9106-GGC-2 with M9000-520 linkage
+909AGA	M9109-AGA-2 with M9000-520 linkage
+909AGC	M9109-AGC-2 with M9000-520 linkage
+909GGA	M9109-GGA-2 with M9000-520 linkage
+909GGC	M9109-GGC-2 with M9000-520 linkage
+923AGA or +943AGA	VA9203-AGA-2Z
+923AGB or +943AGB	VA9203-AGB-2Z
+923BUA or +943BUA	VA9203-BUA-2
+923BUB or +943BUB	VA9203-BUB-2
+923BGA or +943BGA	VA9203-BGA-2
+923BGB or +943BGB	VA9203-BGB-2
+923GGA or +943GGA	VA9203-GGA-2Z
+923GGB or +943GGB	VA9203-GGB-2Z
+928AGA or +948AGA	VA9208-AGA-2
+938AGC or +958AGC	VA9208-AGC-3
+938BAA or +958BAA	VA9208-BAA-3
+938BAC or +958BAC	VA9208-BAC-3
+938BGA or +958BGA	VA9208-BGA-3
+938BGC or +958BGC	VA9208-BGC-3
+928GGA or +948GGA	VA9208-GGA-2
+938GGC or +958GGC	VA9208-GGC-3
H9T4AGA	VA9104-AGA-3S with M9000-561 thermal barrier
H9A4AGA	VA9104-AGA-2S with M9000-561 thermal barrier
H9T4IGA	VA9104-IGA-3S with M9000-561 thermal barrier
H9A4IGA	VA9104-IGA-2S with M9000-561 thermal barrier
H9T4GGA	VA9104-GGA-3S with M9000-561 thermal barrier
H9A4GGA	VA9104-GGA-2S with M9000-561 thermal barrier

Factory Assembly Code	Actuator and Accessories being Mounted
H923AGA or H943AGA	VA9203-AGA-2Z with M9000-561 thermal barrier
H923AGB or H943AGB	VA9203-AGB-2Z with M9000-561 thermal barrier
H923BUA or H943BUA	VA9203-BUA-2 with M9000-561 thermal barrier
H923BUB or H943BUB	VA9203-BUB-2 with M9000-561 thermal barrier
H923BGA or H943BGA	VA9203-BGA-2 with M9000-561 thermal barrier
H923BGB or H943BGB	VA9203-BGB-2 with M9000-561 thermal barrier
H923GGA or H943GGA	VA9203-GGA-2Z with M9000-561 thermal barrier
H923GGB or H943GGB	VA9203-GGB-2Z with M9000-561 thermal barrier
H928AGA or H948AGA	VA9208-AGA-2 with M9000-561 thermal barrier
H938AGC or H958AGC	VA9208-AGC-3 with M9000-561 thermal barrier
H938BAA or H958BAA	VA9208-BAA-3 with M9000-561 thermal barrier
H938BAC or H958BAC	VA9208-BAC-3 with M9000-561 thermal barrier
H938BGA or H958BGA	VA9208-BGA-3 with M9000-561 thermal barrier
H938BGC or H958BGC	VA9208-BGC-3 with M9000-561 thermal barrier
H928GGA or H948GGA	VA9208-GGA-2 with M9000-561 thermal barrier
H938GGC or H958GGC	VA9208-GGC-3 with M9000-561 thermal barrier
+924AGA	M9124 AGA-2 with M9000-518 linkage
+924AGC	M9124 AGC-2 with M9000-518 linkage
+924GGA	M9124 GGA-2 with M9000-518 linkage
+924GGC	M9124 GGC-2 with M9000-518 linkage
+92NAGA or +94NAGA	M9220-AGA-3 with M9000-519 linkage
+92NAGC or +94NAGC	M9220-AGC-3 with M9000-519 linkage
+92NBAA or +94NBAA	M9220-BAA-3 with M9000-519 linkage
+92NBAC or +94NBAC	M9220-BAC-3 with M9000-519 linkage
+92NBGA or +94NBGA	M9220-BGA-3 with M9000-519 linkage
+92NBGC or +94NBGC	M9220-BGC-3 with M9000-519 linkage
+92NGGA or +94NGGA	M9220-GGA-3 with M9000-519 linkage
+92NGGC or +94NGGC	M9220-GGC-3 with M9000-519 linkage

For more information visit: [www.johnsoncontrols.com](http://www.johnsoncontrols.com)